

## E<sub>2</sub>O: no servicing between overhauls



## Slack Adjusters

NYAB's automatic, double-acting, AAR-approved slack adjusters for freight car applications require no servicing between overhauls.

Our KRD-482-E and KRD-133-L slack adjuster features include:

- Wear-resistant wipers between sliding parts prevent dirt and moisture from entering unit
- Automatic adjustment for brake shoe and wheel wear with each brake application
- Only two brake applications are needed to adjust for correct clearance after brake shoe replacement
- Control link and actuating lever hole clearance allows for 6° of axial alignment in all directions between the slack adjuster and the control rod / actuating link
- Corrosion protection on all parts
- KRD-482-E (body mounted brake applications) take up capacity – 19" (482 mm)
- KRD-133-L (truck mounted brake applications) take up capacity – 5-1/4" (133 mm)

Designed for body mounted brake applications, our KRD-482-E slack adjuster is also available in the Water Resistant version with the following additional features:

- Drain holes on both ends to allow condensation to escape
- Zinc-nickel plating on tension rod to improve corrosion resistance
- Improved seals on both ends of slack adjuster to prevent contamination
- Tension rod support to prevent seal wear and prolong service life
- Added O-rings to help prevent water ingress
- Nitrile sealing rings with an integral wasp excluder to prevent foreign debris from entering through the drain hole